



**RC GH**

DN / ID		length [mm]	T [mm]	movements					Max.pressure [kgf/cm <sup>2</sup> ]
[inch]	[mm]			axial [mm]		lateral [mm]	angular [°]		
				comp.	- ext.	+	±	±	
2	50	200-500	5-8	40	15	30	6	1	
2 ½	65	200-500	5-8	40	15	30	6	1	
3	80	200-500	5-8	40	15	30	6	1	
4	100	200-500	5-8	40	15	30	6	1	
5	125	200-500	5-8	40	15	30	6	1	
6	150	200-500	5-8	40	15	30	6	1	
7	175	200-500	5-8	40	15	30	6	1	
8	200	200-500	5-8	40	15	30	6	1	
10	250	200-500	5-8	40	15	30	6	1	
12	300	200-500	5-8	40	15	30	6	1	
14	350	200-700	5-8	40	15	30	6	1	
16	400	200-700	5-8	40	15	30	6	1	
18	450	200-700	5-8	40	15	30	6	1	
20	500	200-700	5-8	40	15	30	6	1	
22	550	250-700	5-8	40	15	30	6	1	
24	600	250-700	5-8	40	15	30	6	1	

Applications:	paper industry and another using of abrasive medium, protecting equipment against vibrations, food industry, plant construction, pipeline with pumps and vessels
Design:	cylindrical rubber sleeve – hose, with/without stainless steel wire, for clamped fixing
Rubber materials:	EPDM, Neopren, Nitril, Hypalon, Natural, Buthyl HT, EPDM HT, EPDM Wras
Accessories:	protective covers or safety hood
Notes:	Other specification on request Technical changes reserved.